


# Straightening Concept **PATCONTROL PCS-15/GRMM**


The fusion of camera based pattern recognition with the fastest responding mechanical weft straightener for

- Automatic pattern detection,
- Distortion correction and
- Design-repeat control



# PATCONTROL PCS

## Pattern & distortion detection, design-repeat



The manufacture and finishing of modern textiles poses problems that were rarely, if ever, encountered previously. It has become far more difficult to turn out straight or realigned patterns. Keeping variables such as design repeat or pattern distortions to within increasingly tighter tolerances is mandatory in the manufacturing, processing and finishing sectors. Distorted patterns especially on lace fabric, carpeting and printed fabric, must be straightened without fail. Bowed or skewed designs impair a product's visual appearance, reduce its usable value and lead to complaints.

### Principle of operation

A PATCONTROL is configured in accordance with each customer's specific requirements.

It differs in accordance with the type of software analysis:

- ✓ One software package detects and controls bowed and skewed designs (PDS Pattern Distortion System)
- ✓ Another software package monitors and controls design repeat (PRS Pattern Repeat System)

The system registers the lie of the pattern by line cameras – the number dependent on repeat size and width of the product – monitors design repeat automatically and continuously, measures the width of the material, and realigns the pattern with the help of an associated straightening machine.

The system detects the repeat length and controls automatically the overfeed setting on the stenter. A clever algorithmic feed forward controller ensures outstanding results. Even with brief variations in repeat length, the overfeed setting is immediately adjusted to the necessary value as soon as the product arrives at the stenter in-feed. By automatically rechecking the result at the delivery end, the PATCONTOL helps to ensure a very stable repeat length on the product.


### Product highlights

- ✓ Modular assembly
- ✓ Measures repeat and straightens patterns simultaneously
- ✓ The very latest high-tech line cameras
- ✓ Easy to retrofit
- ✓ User-friendly

### Customer benefits

- ✓ Uninterrupted monitoring and logging of actual product quality
- ✓ Increased productivity
- ✓ Optimized quality assurance
- ✓ Optimized process repeatability
- ✓ Short payback times
- ✓ Effective also with asymmetric distortions

In order to project the best possible, computable image of the pattern or fabric structure onto the screen, the line cameras are supported by a special light fitting, the beam of which either penetrates or illuminates the surface of the product. Depending on whether the system is required to compute cross-sheet patterns or motion and carriageway repeat, different algorithmic assessments are employed. These depend in turn on the design itself (e.g. pattern, lines, etc.)



A variable number of line cameras are responsible for the image capturing.



- PRS-software for pattern repeat measurement and control

- PDS-software for pattern distortion measurement and control

# ORTHOPAC GRMM

## Product highlights

- ✓ Ultra-precise realignment of pattern
- ✓ Quick reacting servo-controller
- ✓ Progressive rate of straightening
- ✓ Exceedingly compact construction
- ✓ Low product content
- ✓ Wide variety of optional extras

## Distortion correction

For the needful correction of the measured pattern distortion, Mahlo can provide the user with an ORTHOPAC GRMM straightener (=reinforced version for higher line tensions), a universal and well-proven system. Distortions are eliminated with the utmost precision and instantaneously by the interplay between ORTHOPAC GRMM and PATCONTROL PCS. The system is easy to operate and robustly constructed.


The exceedingly compact machine is furnished as standard with 2 skew and 2 bow rollers. A third skew and bow roller can be intergartered optionally. The unique, stepless controlled actuators for adjustment of the bow and skew rollers ensure the quickest possible and most precise response along with an absolute minimum of maintenance.


The compact, reinforced and solid construction of the mechanical straightener is especially suitable for high fabric tensions. Processing speeds range from 3 m/min to 100 m/min. A variety of options ensures that the system can be adapted optimally to suit the respective application and types of product likely to be encountered.

## Customer benefits


- ✓ Maintains tight distortionrelated tolerances
- ✓ Helps avoid complaints
- ✓ Improves customer relationships
- ✓ High standards of repeatability
- ✓ Short payback times
- ✓ Highly reliable / long service life

## A typical installation:





Weft straightener  
ORTOPAC GRMM, with two  
bow and three skew rollers,  
web tension control and  
spreader rollers available as  
optional extras




Straightening capacity of skew and bow rollers

Straightening capacity for  
skew and bow rollers.



## Technical Data

Unit	Patcontrol PCS
Measurement	Optical measurement method by cameras
Max. product width	Up to 5,00 m
Max. line-speed	120 m/min, subject to resolution and lighting
Max. length of camera cable	20 m
Motion sensor	5000 Imp/Rev Dimensions
Subject to product width Power supply	1 ~ 230/115 V AC, 50/60 Hz
Ambient temperature	Max. 50 °C

System mit zwei Kameras  
System with two cameras




System mit einer Kamera  
System with one camera



b = Warenbreite / product width

## Technical Data

Straightener	Orthopac GRMM
Mechanics	2-skew rollers (3rd optional), 2-bow rollers (3rd optional)
Drive mechanism	Hydraulic: controlled by a servo system; Electrical: controlled by frequency-regulated servo motors
Straightening capacity (at w = 1800mm)	Max. skew $\pm$ 540 mm; max. bow $\pm$ 300 mm (2-bow rollers), (with 3-bow or skew rollers +50% each)
Rate of roller adjustment	bow/skew adjustable, minimum of 4-5 seconds at maximum displacement
Max. fabric width	5500 mm
Max. fabric line-speed	150 m/min (no tension control), 150 m/min (with tension control)
Fabric capacity (basic machine with scanner assembly)	2-bow and 2-skew rollers: ~ 3500 mm 3-bow and 3-skew rollers: ~ 4900 mm
Dimensions	See diagrams
Weight (at w = 1800mm)	~ 3900 kg
Power supplies	3 ~ 380V/50Hz, 3 ~ 400V/50Hz, no neutral; transformer available for other voltages
Power consumption	Max. 6,4 kVA (by fully furnished combi-installations)
Ambient temperature	Max. 45°C (no air conditioner)



Orthopac GRMM with Patcontrol PCS  
91-017570



**Monitoring and control systems, automation:**

# MAHLO® GUARANTEES QUALITY. WORLDWIDE, IN YOUR VICINITY.

**Best-possible technical support and transfer of know-how are written in capital letters at Mahlo. Thanks to an international network of agencies and service centres, customers have at their disposal competent support worldwide. We are there for you 365 days a year, 24 hours a day. Just get in touch with us!**

- ✓ Over 40 service centres worldwide
- ✓ Prompt service and supply of spare parts within 24 hours
- ✓ Remote diagnostic system
- ✓ Service-hotline: +49-180-5062456



**Mahlo GmbH + Co. KG Germany**

Donaustr. 12, 93342 Saal/Donau

Tel.: +49-9441-601-0

Fax: +49-9441-601-102

info@mahlo.com

**Mahlo Italia S.R.L. Italy**

Via Fiume 62, 21020 Daverio

Tel.: +39-03-32-94-95-58

Fax: +39-03-32-94-85-86

mahlo.italia@mahlo.com

**Mahlo America Inc. USA**

P.O. Box 2825, Spartanburg, S.C. 29304

Tel.: +1-864-576-62-88

Fax: +1-864-576-00-09

mahlo.america@mahlo.com

**Mahlo España S.L. Spain**

C/ Santa Margarida, s/n - Nave nº13

Polígono Industrial Riera de Caldes - Boada Vell

E08184 Palau Solità i Plegamans (Barcelona)

Tel.: +34-938-640-549

mahlo.espana@mahlo.com

**Mahlo Ouest S.R.L. Belgium**

Quartum Center

Hütte 79 - Bte 10

4700 Eupen

Tel.: +32-87-59-69-00

Fax: +32-87-59-69-09

mahlo.ouest@mahlo.com

**WWW.MAHLO.COM**



Quality made  
in Germany